

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 September 2004 (02.09.2004)

PCT

(10) International Publication Number
WO 2004/075582 A1

(51) International Patent Classification⁷: **H04Q 7/30**

(21) International Application Number:
PCT/CA2004/000300

(22) International Filing Date: 23 February 2004 (23.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/448,459 21 February 2003 (21.02.2003) US

(71) Applicant: **NORTEL NETWORKS LIMITED**
[CA/CA]; 2351 Alfred-Nobel Boulevard, St. Laurent, Quebec H4S 2A9 (CA).

(72) Inventors: **RABIPOUR, Rafi**; 5745 Blossom Avenue, Côte St-Luc, Quebec H4W 2T2 (CA). **CHU, Chung-Chung**; 9370 Rameau, Brossard, Quebec J4X 2M3 (CA).

(74) Agents: **GEORGIEV, Stephan, P.** et al.; Smart & Biggar, 1000 de la Gauchetière Street West, Suite 3400, Montreal, Quebec H3B 4W5 (CA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DATA COMMUNICATION APPARATUS AND METHOD FOR ESTABLISHING A CODEC-BYPASS CONNECTION



(57) Abstract: Communication apparatus having interfaces for exchanging data with first and second neighbors, a memory for storing codec information regarding the communication apparatus and a control entity operative to detect a message from the first neighbor, the first message being indicative of codec information regarding an originating entity. In response, the control entity assesses compatibility between the codec information regarding the originating entity and the codec information regarding the communication apparatus. If the assessment is positive, the control entity self-identifies the communication apparatus as a candidate for terminally supporting a subsequent codec-bypass negotiation with the originating entity. If the assessment is negative, the control entity self-identifies the communication apparatus as a candidate for non-terminally supporting such negotiation. The invention thus capitalizes on the realization that although an end-to-end codec-bypass connection may not be possible, it may nevertheless be possible to achieve bandwidth savings by establishing a codec-bypass connection along only a portion of the path.

WO 2004/075582 A1

DATA COMMUNICATION APPARATUS AND METHOD FOR ESTABLISHING A CODEC-BYPASS CONNECTION

FIELD OF THE INVENTION

5

The present invention relates generally to communications networks and, more particularly, to methods and apparatus for increasing the service quality and efficiency with which data is communicated between entities in such networks.

10 ***BACKGROUND OF THE INVENTION***

According to most existing telecommunications standards, the transmission of speech information over a wireless interface takes the form of compressed speech parameters. Upon receipt of compressed speech parameters at a base station in communication with a
15 mobile unit, the speech parameters are processed by a codec (coder / decoder), which converts (expands) the speech parameters into speech samples, typically at a rate of 64 kilobits per second (kb/s) in order to provide compatibility with the public switched telephone network (PSTN). The speech samples at 64 kb/s are then transmitted over the PSTN towards the called party. The speech samples associated with a given call may share
20 the same link as speech samples associated with other calls by virtue of time division multiplexing (TDM), which provides for fixed-duration time slots to be allotted to individual calls.

If the called party is connected directly to the PSTN, such as via a wireline connection, the
25 speech samples having travelled through the network will simply be converted into audio form by a digital telephone unit at the called party site. Of course, the called party may also be a second mobile unit, in which case the speech samples will terminate at a second base station, where a second codec re-converts the speech samples back into compressed speech parameters for transmission to the second mobile unit via a wireless interface. The usage of
30 a source decoder to expand speech parameters into a stream of speech samples, in combination with the use of a destination encoder for re-compression of these samples into a second set of compressed speech parameters, is referred to as operation of codecs in tandem, or "tandem operation".

Those skilled in the art will appreciate that when both the called and calling parties are mobile units, the tandem operation described above introduces a degradation in service quality, as errors may be introduced by the decompression and re-compression operations performed by the source and destination codecs, respectively. Such error should in principle be avoidable, as neither codec operation is required by virtue of the second base station requiring the compressed speech parameters rather than the expanded speech samples. Thus, it is of interest to find a solution to the problem of service quality in call connections involving tandem codecs.

Two classes of solutions to the problem relating to the service quality in call connections involving tandem codecs have already been described and standardized, or are well in their way towards standardization. The earlier of the two methods, called Tandem-Free Operation (TFO), uses an in-band handshaking protocol to detect the presence of tandem codecs, and then proceeds to insert the compressed speech parameters within the 64 kb/s sample stream. This arrangement bypasses the requirement for decompression at the source codec and (re-)compression at the destination codec, which obviates the occurrence of errors at these two stages. As a result, a high quality of service can be achieved for a given end-to-end call between two mobile units. However, the standardized TFO approach provides no bandwidth advantage, as the full bandwidth ordinarily needed for the 64 kb/s sample stream is consumed for transmission of the compressed speech parameters.

A more recent approach, called Transcoder-Free Operation (TrFO), uses out-of-band signaling to detect call scenarios involving tandem codecs at call set-up time. Thereupon action is taken to put in place a direct end-to-end link to provide for a direct exchange of the compressed speech parameters without the involvement of network transcoders. However, while it provides for a savings and resource reduction compared to the standardized TFO approach, the TrFO implementation suffers from the disadvantage of added cost and complexity due to, for example, the requirement for out-of-band signaling.

For more information on the TFO and TrFO techniques, the reader is invited to refer to the following documents that are hereby incorporated by reference:

- 3rd generation partnership project, Technical specification group core network, Out of band transcoder control – Stage 2 (3GPP TS 23.153 V4.4.0 (2001-12));
- 3rd generation partnership project, Technical specification group core network, Bearer-independent circuit-switched core network, Stage 2 (3GPP TS 23.205 V4.4.0 (2002-03));
- 3rd generation partnership project, Technical specification group (TSG) RAN3, Transcoder free operation (3GPP TR 25.953 V4.0.0 (2001-03));
- 3rd generation partnership project, Technical specification group services and system aspects, Inband tandem free operation (TFO) of speech codecs, service description – Stage 3 (3GPP TS 28.062 V5.0.0 (2002-03));

It will thus be apparent that there is a need in the industry to provide a solution that is as robust and easy to implement, while also providing bandwidth and resource savings.

Moreover, the use of conventional codec-bypass schemes such as TFO has heretofore been limited to enhancing the quality of calls established between two suitably enabled base station units in a mobile-to-mobile call. When one party is not so enabled, e.g., a telephone connected to a common packet-switched network via a network gateway, the use of conventional codec-bypass techniques is not possible. It would therefore be an advantage to exploit the ability of one party's codec-bypass capabilities, even when the other party is not a suitably enabled base station unit.

In addition, the use of conventional codec-bypass schemes is often limited by the use of backhaul gateways in a network, even when both parties to a call are codec-bypass-enabled base station units. Such gateways compress speech samples into a different format prior to transmittal of the formatted speech samples over a network. Unfortunately, when codec-bypass information is carried within the bit structure of the speech samples, the compression effected by a backhaul gateway results in loss of the information and hence prevents advantageous usage of this facility. Hence, it would be beneficial to be able to allow tandem-free operation in circumstances where a backhaul gateway is used.

SUMMARY OF THE INVENTION

The present invention realizes that although an end-to-end codec-bypass connection along a given path between two endpoints may not be possible, it is nevertheless possible to achieve bandwidth savings by establishing a codec-bypass connection along only a portion of the path.

5

Therefore, according to a first broad aspect, the invention seeks to provide a communication apparatus, comprising a first interface for exchanging data with a first neighboring entity, a second interface for exchanging data with a second neighboring entity, a memory for storing codec information regarding the communication apparatus and a control entity
10 operative to detect a first message from the first neighboring entity via the first interface, the first message being indicative of codec information regarding an originating entity. Responsive to detection of the first message, the control entity is operative to perform an assessment of compatibility between the codec information regarding the originating entity and the codec information regarding the communication apparatus. Responsive to the
15 assessment of compatibility being positive, the control entity is operative to self-identify the communication apparatus as a candidate for terminally supporting a subsequent codec-bypass negotiation with the originating entity. Responsive to the assessment of compatibility being negative, the control entity is operative to self-identify the communication apparatus as a candidate for non-terminally supporting a subsequent codec-
20 bypass negotiation with the originating entity.

According to a second broad aspect, the invention seeks to provide a method of establishing candidacy of a gateway as terminally or non-terminally supporting a codec-bypass negotiation with an originating entity in a communications network. The method comprises
25 detecting a first message received from a first neighboring entity, the first message being indicative of codec information regarding the originating entity; assessing compatibility between the codec information regarding the originating entity and the codec information regarding the gateway; responsive to the assessment of compatibility being positive, self-identifying the gateway as a candidate for terminally supporting a subsequent codec-bypass
30 negotiation with the originating entity; and, responsive to the assessment of compatibility being negative, self-identifying the gateway as a candidate for non-terminally supporting a subsequent codec-bypass negotiation with the originating entity.

The invention also seeks to provide, in accordance with a third broad aspect, computer-readable media tangibly embodying a program of instructions executable by a computer to perform the above method of establishing candidacy of a gateway as terminally or non-terminally supporting a codec-bypass negotiation with an originating entity in a communications network.

According to a fourth broad aspect, the present invention seeks to provide a method of establishing a codec-bypass connection between a first gateway and one of a plurality of in-path gateways located along a path from the first gateway to a second gateway. The method comprises identifying a target in-path gateway from among the plurality of in-path gateways, the target in-path gateway being the in-path gateway furthest along the path from the first gateway which is characterized by codec-bypass connection compatibility with the first gateway, and establishing a codec-bypass connection between the first gateway and the target in-path gateway.

The invention may also be summarized according to a fifth broad aspect as seeking to provide a method of establishing a codec-bypass connection along a path between a first gateway and a second gateway, the path comprising a plurality of in-path gateways. The method comprises identifying a first sub-path between the first gateway and a first target in-path gateway from among the plurality of in-path gateways, the first target in-path gateway being the in-path gateway furthest along the path from the first gateway which is characterized by codec-bypass connection compatibility with the first gateway. The method also comprises identifying a second sub-path between the second gateway and a second target in-path gateway from among the plurality of in-path gateways, the second target in-path gateway being the in-path gateway furthest along the path from the second gateway which is characterized by codec-bypass connection compatibility with the second gateway. The method further comprises determining the lengths of the first and second sub-paths and, if the first sub-path is longer than the second sub-path, establishing a codec-bypass connection between the first gateway and the first target gateway, otherwise if the second sub-path is longer than the first sub-path, establishing a codec-bypass connection between the second gateway and the second target gateway.

These and other aspects and features of the present invention will now become apparent to those of ordinary skill in the art upon review of the following description of specific embodiments of the invention in conjunction with the accompanying drawings.

5 ***BRIEF DESCRIPTION OF THE DRAWINGS***

In the accompanying drawings:

10 Figs. 1A to 1D shows various call scenarios to which embodiments of the present invention are applicable;

15 Fig. 2 is a message flow diagram illustrating various steps in establishing a codec-bypass connection in the scenario of Fig. 1A, in accordance with a specific embodiment of the present invention; and

20 Figs. 3 to 8 show various alternative configurations to which embodiments of the present invention are applicable.

25 ***DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS***

20 In accordance with an embodiment of the present invention, arbitrary combinations of wireless / wireline gateways collaborate constructively to reduce bandwidth and delay, and to achieve higher voice quality by removing – to the extent possible – tandem codecs (or vocoders). The present description herein below describes a method to resolve the
25 disposition of the gateways that could find themselves involved in an codec-bypass connection. The gateways being given consideration are those which modify the speech payload (e.g. transcoding between different codec formats, including G.711).

30 With reference to Fig. 1A, a connection (e.g., a telephone call) is established between two endpoints A, B in a network consisting of a plurality of communication apparatuses hereinafter referred to as gateways. The network in question may include a circuit-switched network (e.g., the public switched telephone network – PSTN), a packet network or a

combination thereof. Each of the endpoints A, B of the call may be either of a mobile station (wireless) or a land-based unit (wireline).

Various types of gateways are traversed by the call as it travels along subsequent legs of a call from one endpoint to another. The following definitions of various types of gateways have been provided for purposes of clarity, but without any intent to limit or otherwise restrict the scope of the present invention.

In particular, a "TDM gateway" is defined as a gateway that connects a circuit-switched network to a packet network. A "packet gateway" is defined as a gateway that connects only to a packet network. An "endpoint gateway" (or "termination gateway") is defined as a gateway located at an extreme end of the signal path. An example of an endpoint gateway is a UMTS gateway. In Fig. 1A, endpoint gateways include gateways A and B. Finally, an "in-path gateway" is defined as a gateway that is an intermediate node in the signal path (i.e. not an endpoint gateway). In Fig. 1A, in-path gateways include gateways 1, 2 and 3.

In general, a gateway comprises communications interfaces for communicating with neighbouring entities. In the case of an in-path gateway, the neighbouring entities are other gateways. Each gateway is configured to exchange signals in a variety of formats that are defined by a set of codecs with which the gateway is associated. Accordingly, each gateway is equipped with a memory element for storing codec information regarding the gateway in question. In the example of Fig. 1A, gateways A, 1 and 3 are associated with codec X, while gateway 2 is associated with codec Y and gateway B is associated with codec Z. It is noted that each gateway may be associated with more than one codec.

Once a call is established between the endpoints, the endpoint gateways attempt to establish a codec-bypass connection. This attempt is made through the exchange of codec-bypass negotiation messages during a codec-bypass negotiation. If the two endpoint gateways are associated with a common codec, then an end-to-end codec-bypass connection can indeed be established through codec-bypass negotiation (or "dialogue"). This provides significant quality enhancement.

When the two endpoint gateways are not associated with a common codec, then one may have recourse to a procedure whereby a codec-bypass connection is negotiated (“dialogued”) for only a portion of the path that joins the endpoint gateways. This procedure, which is described in greater detail herein below, results in bandwidth savings and quality enhancement compared with the case where an attempt at establishing end-to-end codec-bypass mode of operation would be altogether abandoned. In a specific embodiment, the gateways along the path joining the endpoint gateways negotiate a codec-bypass mode of operation connection for the longest possible portion of that path.

It is assumed, for the purposes of description, that the various in-path gateways along the path are at least minimally codec-bypass compliant, without necessarily being able to terminate a codec-bypass negotiation or connection. Specifically, depending on the particular codec used by a remote entity and on the particular phase of a codec-bypass negotiation, a gateway is assumed to be at least capable of acquiring a “passive” mode. A gateway in “passive” mode is capable of relaying codec-bypass negotiation messages from one leg to another leg of a call that it serves, but it does not terminate the negotiation, i.e., it only serves to “passively support” a codec-bypass negotiation. However, depending on the capabilities of the gateway, the gateway may also be able to acquire an “active” mode for the purposes of the codec-bypass negotiation. In “active” mode, the gateway is capable of terminally supporting (i.e., terminating) a codec-bypass negotiation on at least one leg of a call that it serves. Thus, the gateway thus operates differently in passive mode and in active mode, assuming that the active mode can be acquired for a given codec-bypass negotiation.

Fig. 2 illustrates a non-limitative example of operation of the present invention with respect to the specific scenario in Fig. 1A. The following describes the coordination of the in-path gateways 1, 2, 3 in response to codec-bypass negotiation messages initiated by endpoint gateway A and subsequently exchanged amongst the various other gateways in the path between endpoint gateways A and B. In particular, once a call is established, all codec-bypass-compliant gateways will start monitoring the bearer to detect codec-bypass negotiation messages. In addition to monitoring, those gateways that will have self-identified themselves as active will start transmitting codec-bypass negotiation messages. Optionally, the active in-path gateways can wait for a finite time period before initiating

codec-bypass transmissions. This is meant to give priority to transmissions initiated by endpoint gateways.

Thus, for example, at 220, endpoint gateway A starts by transmitting an initial codec-bypass negotiation message 202. The initial message 202 carries the codec information regarding endpoint gateway A, specifically a list of codec types and configurations supported by endpoint gateway A. In this case, the codec information identifies “codec X” as being supported at endpoint gateway A. Optionally, an endpoint gateway can provide a designated data element (e.g., a single bit) to identify its codec-bypass messages as having emanated from one end of the end-to-end connection in question.

When the i^{th} in-path gateway (denoted GW(i) for convenience) receives the initial message 202 originated from endpoint gateway A, and if the codec type and codec configuration listed in the initial message 202 matches in-path GW(i)’s internally supported codec type and configuration, then in-path gateway GW(i) will return a response message towards endpoint gateway A through in-path gateways GW(i-1), GW(i-2), etc. The purpose of the response message is to signal to in-path gateway GW(i-1) and beyond (towards the endpoint gateway A) that in-path gateway GW(i) has the ability to support a compatible codec type and configuration. In-path gateway GW(i) thus goes through the process of identifying itself as a candidate gateway, capable of terminating the current codec-bypass negotiation with endpoint gateway A. In-path gateway GW(i) therefore self-identifies itself as an “active” gateway. However, as the response message travels towards endpoint gateway A, any previously determined active gateways in the chain will re-self-identify itself as a passive gateway upon receipt of the response message.

For example, at 222, in-path gateway 1, upon receipt of the initial message 202, realizes that it has a compatible codec type and configuration (namely, codec X). This causes the in-path gateway 1 to make a “mental note” of the fact that it is now active, i.e., in-path gateway 1 is now a candidate for terminating the codec-bypass negotiation with endpoint gateway A.

The making of a “mental note” can take many forms, such as self-identification by way of setting a binary flag whose two states correspond to active and passive, respectively. This also results in in-path gateway 1 sending a response message 204 back to the endpoint

gateway A. Meanwhile, gateway 1 forwards the initial message 202 towards in-path gateway 2.

At 224, in-path gateway 2, upon receipt of the initial message 202, realizes that it has does not have a codec type and configuration compatible with "codec X". In-path gateway 2 therefore plays the role of a passive gateway. Under such circumstances, in-path gateway 2 simply forwards the initial message 202 towards in-path gateway 3 without any indication back towards in-path gateway 1.

At 226, in-path gateway 3, upon receipt of the initial message 202, realizes that it has a codec type and configuration compatible with "codec X". Accordingly, the in-path gateway 3 makes a "mental note" of the fact that it is now active, i.e., in-path gateway 3 is now a candidate for eventually terminating the current codec-bypass negotiation with endpoint gateway A. Again, the making of a "mental note" can take many forms, such as self-identification by way of setting a binary flag whose two states correspond to active and passive, respectively. This also results in in-path gateway 3 forwarding the initial message 202 towards endpoint B, while sending a second response message 206 back to the in-path gateway 2.

At gateway 2, being a passive gateway, the second response message 206 is simply forwarded to in-path gateway 1. However, a different effect is produced at in-path gateway 1, which had previously self-identified itself as active. The receipt of the second response message 206 by the in-path gateway 1 sigls to the in-path gateway 1 that a gateway further down the chain towards endpoint gateway B is now active due to its capability of terminating the current codec-bypass negotiation. Therefore, in-path gateway 1 switches its mode of operation to "passive".

The above-described process stops when a particular in-path gateway receives a message, i.e. a codec-bypass message transmitted by endpoint gateway B, or when a self-identified candidate fails to receive any codec-bypass messages, e.g.. due to absence of the endpoint gateway B for end-to-end codec-bypass connection. In the former case, the self-identified candidate will go into passive mode only temporarily, in order to relay the codec-bypass message back towards endpoint gateway A, so as to allow end-to-end codec-bypass

negotiation. If the end-to-end negotiation between endpoint gateways A and B is successful, all in-path gateways, including the one that temporarily went into passive mode, remain in passive mode. However, in the case where there is no end-to-end codec-bypass connection due to a negotiation failure, the last self-identified codec-bypass candidate will
5 transmit a message in an attempt to start a codec-bypass negotiation with endpoint gateway A.

Thus, for example, at 228, endpoint gateway B does not have a codec type and configuration compatible with "codec X". Therefore, endpoint gateway B either does not
10 send a message back to gateway 3, or (as illustrated) endpoint gateway B sends a neg_fail message 208 (negotiation failure) towards in-path gateway 3. Receipt of the neg_fail message 208 and in-path gateway 3 signals to the in-path gateway 3 that it is the furthest gateway from endpoint gateway A that is capable of terminating the codec-bypass negotiation. Accordingly, as shown in Fig. 1A, in-path gateway 3 negotiates a codec-
15 bypass connection with endpoint gateway A.

Of course, it is also possible that no end-to-end codec-bypass connection is possible due to sheer absence of endpoint gateway B. This scenario, shown in Fig. 1B, causes basically the same end result, with the active in-path gateway furthest along the path from endpoint
20 gateway A transmitting a response message in an attempt to start negotiation of a codec-bypass connection with endpoint gateway A.

At the same time that endpoint gateway A attempts to dialogue with gateways further along the path towards endpoint gateway B, endpoint gateway B itself may be attempting to
25 dialogue with gateways further along the path towards endpoint gateway A. By completing analogous processes for both endpoint gateways A and B (and waiting until both options have been explored), a codec-bypass communication with the longest possible span from either endpoint can be established.

As illustrated in Fig. 1C, there also could be a scenario in which the end-to-end codec-bypass negotiation fails due to codec mismatch, but where the possibility of overlap
30 between two possible codec-bypass connections nonetheless exists. The two active in-path gateways (from both ends) have knowledge if the end-to-end mismatch resolution was

attempted or not (e.g., via presence or absence of exchanged request and acknowledge messages). After the active in-path gateways confirm the scenario, a codec-bypass solution can be provided. In short, codec-bypass negotiation between an in-path gateway with a terminating gateway will not be disrupted by a codec-bypass attempt by the remote endpoint gateways.

Specifically, as per the existing codec-bypass decision algorithm or codec mismatch resolution rules, all codecs are ranked in preference. During the scenario being contemplated, there are two incompatible codec types/configurations at endpoint gateways A and B, but each can establish a respective codec-bypass connection with a different one of the in-path gateways (namely in-path gateway 3 with endpoint gateway A and in-path gateway 2 with endpoint gateway B). An active in-path gateway which has identified itself as the codec-bypass candidate for termination of codec-bypass negotiation in one direction but which supports a less preferred codec type/configuration will continue to send a response message (e.g., 204 or 206 in Fig. 2) in order to maintain its candidacy; however, it will refrain from initiating codec-bypass negotiation for a certain delay after the scenario is entered. This is meant to allow an active in-path gateway supporting the preferred codec type / configuration to initiate the codec-bypass negotiation first.

In the example of Fig. 1D, if codec X is preferred to codec Y, then in-path gateway 3 will initiate a codec-bypass negotiation with terminating gateway A while in-path gateways 1 and 2 remain passive. Both in-path gateways 2 and 4 can initiate codec-bypass negotiation with endpoint gateway B after the specified delay. If there is no codec-bypass connection established across in-path gateway 2, in-path gateway 2 may optionally transmit a message to initiate a codec-bypass negotiation with endpoint gateway B. However, as is the case in the illustrated embodiment, a codec-bypass connection is established between endpoint gateway A and in-path gateway 3, which means that in-path gateway 2 self-identifies itself as passive. Therefore, in-path gateway 4 will not receive the response message (204 or 206) from in-path gateway 2 and will therefore remain self-identified as active, i.e., it is a candidate for terminating the codec-bypass negotiation with endpoint gateway B. (This design is applicable to all other in-path gateways in the chain supporting codec Y.) In this manner, the furthest in-path gateway from endpoint B which supports codec Y and is outside the codec-bypass connection between endpoint gateway A and in-path gateway 3 is

sought for the purposes of initiating codec-bypass negotiation with in-path gateway 4. In the illustrated embodiment, this title is held by in-path gateway 4, which supports codec Y and is outside the codec-bypass connection between endpoint gateway A and in-path gateway 3. As a result, two separate non-overlapping codec-bypass connections can be established. Generally speaking, the present invention allows for more than one segment of codec-bypass negotiations.

An in-path gateway that detects codec-bypass negotiation messages only from one "side" (as viewed in the orientation in Figs. 1A-1D and 2) can become a codec-bypass termination point. If codec-bypass transmissions are detected on both sides (labeled "left" and "right" sides for Packet GW, and "packet" and "TDM" for TDM GW), the behavior of (active) gateways is determined based on the mutual vocoder compatibility of the two remote nodes, as well as that of the gateway itself. Tables 1-4 define the behavior of Packet and TDM gateways under specific embodiments of the present invention.

As an enhancement, a data element (e.g., a single bit) can be used to identify cases in which a gateway needs to receive traffic in the "original" compression format (i.e. compression format at the time of call setup – e.g., G.711) even after establishment of a codec-bypass connection. This bit can be used in two cases. Firstly, it will be used by passive gateways to make sure that adjacent gateways will continue to send them the traffic signal in the original format (e.g., G.711) as well as in other compressed formats after the establishment of a codec-bypass connection. Secondly, this bit will also be used by active TDM gateways that may not be able to support the codec selected for establishment of a codec-bypass connection, to request that adjacent gateways continue to send them the traffic signal in the original format (e.g., G.711) as well as in other compressed formats after the establishment of a codec-bypass connection.

Table 1: Packet gateway codec compatibility when adjacent gateways do not require original codec format

5

<p>Legend:</p> <p>GW / Left: This column indicates whether or not the gateway and the “left”-side end node have common codecs</p> <p>GW / Right: This column indicates whether or not the gateway and the “right”-side end node have common codecs</p> <p>Left / Right: This column indicates whether or not the left- and right-side end nodes have common codecs with each other (but not necessarily with the gateway)</p> <p>Y: the two entities have at least one compatible vocoder</p> <p>N: the two entities have no compatible vocoders</p> <p>X: It makes no difference whether or not a compatible vocoder exists</p>			
GW / Left	GW / Right	Left / Right	Resolution
X	X	Y	Gateway is passive towards both end nodes. “Left” and “Right” switch to common codec
Y	Y	N	Depending on the availability of CPU resources, gateway can be active towards either or both end nodes independently to achieve bandwidth and/or delay optimization
N	Y	N	Gateway is active towards right-side end node
Y	N	N	Gateway is active towards left-side end node
N	N	N	Gateway is passive towards both end nodes. Codec-bypass negotiation cannot be terminated with either end.

Table 2: TDM Gateway codec compatibility when adjacent packet gateway and TDM-side node do not require original codec format

5

<p>Legend:</p> <p>GW / Packet: This column indicates whether or not the gateway and the packet-side end node have common codecs</p> <p>GW / TDM: This column indicates whether or not the gateway and the TDM-side end node have common codecs</p> <p>Packet / TDM: This column indicates whether or not the packet- and TDM-side end nodes have common codecs with each other (but not necessarily with the gateway)</p> <p>Y: the two entities have at least one compatible vocoder</p> <p>N: the two entities have no compatible vocoders</p> <p>X: It makes no difference whether or not a compatible vocoder exists</p>			
GW / Packet	GW / TDM	Packet / TDM	Resolution
Y	Y	Y	Gateway is passive towards both end nodes. Packet-side and TDM-side end nodes switch to common codec.
N	N	Y	Gateway is passive towards both end nodes. Codec-bypass negotiation cannot be terminated with either end node, although end-to-end codec-bypass negotiation may transit the gateway. Sets bit to indicate (to packet side) that it requires traffic in the format that was in use at call setup
N	N	N	Gateway is passive towards both end nodes. Codec-bypass negotiation cannot be terminated with either end node

Y	N	N	Gateway is active towards packet-side end node
Y	N	Y	Gateway is active towards packet-side end node. Alternatively, gateway can remain passive to allow codec-bypass negotiation to transit the gateway. In such case, set bit to indicate (to packet side) that traffic is required in the format that was in use at call setup
N	Y	N	Gateway is active towards TDM-side end node
N	Y	Y	Gateway is active towards TDM-side end node. Alternatively, gateway can remain passive to allow codec-bypass negotiation to transit the gateway. In such case, set bit to indicate (to packet side) that traffic is required in the format that was in use at call setup

Table 3: Packet gateway codec compatibility when “left” gateway requires original codec format

5

<p>Legend:</p> <p>GW / Left: This column indicates whether or not the gateway and the “left”-side end node have common codecs</p> <p>GW / Right: This column indicates whether or not the gateway and the “right”-side end node have common codecs</p> <p>Left / Right: This column indicates whether or not the left- and right-side end nodes have common codecs with each other (but not necessarily with the gateway)</p> <p>Y: the two entities have at least one compatible vocoder</p> <p>N: the two entities have no compatible vocoders</p> <p>X: It makes no difference whether or not a compatible vocoder exists</p>			
GW / Left	GW / Right	Left / Right	Resolution

Y	Y	Y	Gateway is active towards the right-side end node and towards the left-side end node
Y	N	Y	Gateway is passive towards both end nodes. Sets special bit towards "right" to indicate the need to support original codec format. Codec-bypass negotiation will transit the gateway
N	Y	Y	Gateway is passive towards both end nodes. Sets special bit towards "right" to indicate the need to support original codec format. Codec-bypass negotiation will transit the gateway. Alternatively, gateway can be active towards the right-side end node
N	N	Y	Gateway is passive towards both end nodes. Sets special bit towards "right" to indicate the need to support original codec format. Codec-bypass negotiation will transit the gateway
N	N	N	Gateway is passive towards both end nodes. Codec-bypass negotiation cannot be terminated with either end node
Y	N	N	Gateway will be active towards the left-side end node
N	Y	N	Gateway will be active towards the right-side end node
Y	Y	N	Depending on CPU availability, gateway will be active towards the left-side end node and/or the right-side end node

Table 4: TDM gateway codec compatibility when adjacent packet gateway requires original codec format

5

<p>Legend:</p> <p>GW / Packet: This column indicates whether or not the gateway and the packet-side end node have common codecs</p> <p>GW / TDM: This column indicates whether or not the gateway and the TDM-side end node have common codecs</p> <p>Packet / TDM: This column indicates whether or not the packet- and TDM-side end nodes have common codecs with each other (but not necessarily with the gateway)</p> <p>Y: the two entities have at least one compatible vocoder</p> <p>N: the two entities have no compatible vocoders</p> <p>X: It makes no difference whether or not a compatible vocoder exists</p>			
GW / Packet	GW / TDM	Packet / TDM	Resolution
Y	Y	Y	Gateway is passive towards both end nodes
N	N	Y	Gateway is passive towards both end nodes. Codec-bypass negotiation cannot be terminated with either end node, although end-to-end codec-bypass negotiation may transit the gateway. Sets bit to indicate (to packet side) that it requires traffic in the format that was in use at call setup
N	N	N	Gateway is passive towards both end nodes. Codec-bypass negotiation cannot be terminated with either end
Y	N	N	Gateway is active towards the packet-side node
Y	N	Y	Gateway is active towards packet-side end node.

			Alternatively, gateway can remain passive to allow codec-bypass negotiation to transit the gateway. In such case, set bit to indicate (to packet side) that traffic is required in the format that was in use at call setup
N	Y	N	Gateway is active towards the TDM-side node
N	Y	Y	Gateway is active towards TDM-side end node. Alternatively, gateway can remain passive to allow codec-bypass negotiation to transit the gateway. In such case, set bit to indicate (to packet side) that traffic is required in the format that was in use at call setup
Y	Y	N	Depending on the availability of CPU resources, gateway can be active towards either or both end nodes independently to achieve bandwidth and/or delay optimization

It should be understood that other modifications of, and additions to, the present invention are possible. For example, the self-identification process described herein above is applicable to the various example, non-limiting scenarios depicted in Figs. 3 to 8.

Also, it is recalled that the rules and procedures above essentially lead to clarification of a particular in-path gateway's disposition. Specifically, a codec-bypass-compliant in-path gateway will know whether or not it is the last in-path gateway and whether or not it has vocoders common with each of the endpoints. Equipped with this information, should a codec-bypass connection fail to establish due to the absence of a compatible codec type or configuration at either end, the above methods can be applied recursively in order to come up with codec-bypass connection segments where applicable, for the purpose of reducing bandwidth where applicable. The recursive application of the procedure means that the last in-path gateways (rather than the endpoint gateways) would initiate their own search for codec-bypass partners based on their full suite of supported vocoders. In initiating the

codec-bypass handshaking these gateways will also take advantage of their knowledge of the vocoders supported by the endpoints to achieve maximum bandwidth savings and voice quality. A pre-defined vocoder order of preference will guide the application of the procedure, e.g., in situations where each of the two last in-path gateways supports the vocoder of different endpoints only. The prescribed order of vocoder preference will determine which of the two last in-path gateways will initiate the new round of codec-bypass handshaking. The in-path gateway which supports a vocoder with a lower priority will wait for a prescribed period of time before initiating its own codec-bypass handshaking. This priority scheme prevents race conditions that may lead to instability.

Should the procedure initiated by the last in-path gateways fail to achieve codec-bypass mode of operation due to the absence of common vocoders, the recursion can be applied again to search for yet more limited application of codec-bypass mode of operation. Thus, the in-path gateways can identify themselves to be in the middle of the path, rather than the last in-path gateway, by monitoring codec-bypass exchanges around them including the usage of a suitable message. Again, the procedure may result in several segments of codec-bypass negotiations, i.e. not limited to a single segment.

Those skilled in the art will appreciate that the control entity of each gateway may be implemented as an arithmetic and logic unit (ALU) having access to a code memory (not shown) which stored program instructions for the operation of the ALU. The program instructions could be stored on a medium which is fixed, tangible and readable directly by the processor, (e.g., removable diskette, CD-ROM, ROM, or fixed disk), or the program instructions could be stored remotely but transmittable to the processor via a modem or other interface device (e.g., a communications adapter) connected to a network over a transmission medium. The transmission medium may be either a tangible medium (e.g., optical or analog communications lines) or a medium implemented using wireless techniques (e.g., microwave, infrared or other transmission schemes).

Those skilled in the art should also appreciate that the program instructions stored in the code memory can be compiled from a high level program written in a number of programming languages for use with many computer architectures or operating systems. For example, the high level program may be written in assembly language, while other

versions may be written in a procedural programming language (e.g., "C") or an object oriented programming language (e.g., "C++" or "JAVA").

Those skilled in the art should further appreciate that in some embodiments of the invention,
5 the functionality of the control entity may be implemented as pre-programmed hardware or firmware elements (e.g., application specific integrated circuits (ASICs), electrically erasable programmable read-only memories (EEPROMs), etc.), or other related components.

10 While specific embodiments of the present invention have been described and illustrated, it will be apparent to those skilled in the art that numerous modifications and variations can be made without departing from the scope of the invention as defined in the appended claims.

WE CLAIM:

1. A communication apparatus, comprising:

- a first interface for exchanging data with a first neighboring entity;
- 5 - a second interface for exchanging data with a second neighboring entity;
- a memory for storing codec information regarding said communication apparatus;
- a control entity operative to detect a first message from the first neighboring entity via the first interface, the first message being indicative of codec information regarding an originating entity;
- 10 - responsive to detection of the first message, the control entity being operative to perform an assessment of compatibility between the codec information regarding the originating entity and the codec information regarding said communication apparatus;
- responsive to the assessment of compatibility being positive, the control entity being
15 operative to self-identify the communication apparatus as a candidate for terminally supporting a subsequent codec-bypass negotiation with the originating entity;
- responsive to the assessment of compatibility being negative, the control entity being operative to self-identify the communication apparatus as a candidate for non-terminally supporting a subsequent codec-bypass negotiation with the originating
20 entity.

2. The communication apparatus defined in claim 1, further comprising:

- responsive to the assessment of compatibility being positive, the control entity being further operative to release a second message towards the first neighboring
25 entity via the first interface, the second message being indicative of the communication apparatus being self-identified as a candidate for terminally supporting a subsequent codec-bypass negotiation with the originating entity.

3. The communication apparatus defined in claim 1, further comprising:

- 30 - responsive to absence of any message from the second entity indicative of the second entity being self-identified as a candidate for terminally supporting a subsequent codec-bypass negotiation with the originating entity, effecting said subsequent codec-bypass negotiation with the first entity.

4. The communication apparatus defined in claim 1, further comprising:
- the control entity being operative to forward the first message to the second remote entity via the second interface.

5

5. The communication apparatus defined in claim 1, wherein the first and second interfaces are packet interfaces.

10

6. The communication apparatus defined in claim 1, wherein the first interface is a packet interface and the second interface is a circuit-switched interface.

7. The communication apparatus defined in claim 1, wherein the first and second interfaces are circuit-switched interfaces.

15

8. The communication apparatus defined in claim 1, the control entity being further operative to:

20

- detect a second message received from the second neighboring entity, the second message being indicative of the second neighbouring entity apparatus being self-identified as a candidate for terminally supporting a subsequent codec-bypass negotiation with the originating entity;
- responsive to detection of the second message, self-identify the communication apparatus as a candidate for non-terminally supporting a subsequent codec-bypass negotiation with the originating entity.

25

9. The communication apparatus defined in claim 8, further comprising:

- the control entity being operative to forward the second message to the first remote entity via the first interface.

30

10. The communication apparatus defined in claim 8, further comprising:

- the control entity being further operative to monitor messages exchanged via the first and second interfaces that are indicative of negotiation of a codec-bypass connection between the originating entity and an entity different from the originating entity.

11. The communication apparatus defined in claim 10, said negotiation being a first negotiation, wherein the control entity is further operative to:

- detect success or failure of said first negotiation; and
- responsive to failure of said first negotiation, and if the communication apparatus is self-identified as a candidate for terminally supporting a subsequent codec-bypass negotiation with the originating entity, negotiate with the originating entity a codec-bypass connection between the communication apparatus and the originating entity.

12. The communication apparatus defined in claim 11, further comprising:

- responsive to success of said first negotiation, and if the communication apparatus is self-identified as a candidate or terminally supporting a subsequent codec-bypass negotiation with the originating entity, the control entity being operative to self-identify the communication as a candidate for non-terminally supporting a codec-bypass negotiation with the originating entity.

13. The communication apparatus defined in claim 10, said negotiation being a first negotiation, wherein the control entity is further operative to:

- detect success or failure of said first negotiation; and
- responsive to success of said first negotiation, and if the communication apparatus is self-identified as a candidate or terminally supporting a subsequent codec-bypass negotiation with the originating entity, the control entity being operative to self-identify the communication as a candidate for non-terminally supporting a codec-bypass negotiation with the originating entity.

14. The communication apparatus defined in claim 11, wherein the originating entity is an endpoint gateway.

15. The communication apparatus defined in claim 11, wherein the originating entity is an in-path gateway.

16. A method of establishing candidacy of a gateway as terminally or non-terminally supporting a codec-bypass negotiation with an originating entity in a communications network, comprising:

- detecting a first message received from a first neighboring entity, the first message being indicative of codec information regarding the originating entity;
- assessing compatibility between the codec information regarding the originating entity and the codec information regarding the gateway;
- responsive to the assessment of compatibility being positive, self-identifying the gateway as a candidate for terminally supporting a subsequent codec-bypass negotiation with the originating entity;
- responsive to the assessment of compatibility being negative, self-identifying the gateway as a candidate for non-terminally supporting a subsequent codec-bypass negotiation with the originating entity.

17. Computer-readable media tangibly embodying a program of instructions executable by a computer to perform a method of establishing candidacy of a gateway as terminally or non-terminally supporting a codec-bypass negotiation with an originating entity in a communications network, the method comprising:

- detecting a first message received from a first neighboring entity, the first message being indicative of codec information regarding the originating entity;
- assessing compatibility between the codec information regarding the originating entity and the codec information regarding the gateway;
- responsive to the assessment of compatibility being positive, self-identifying the gateway as a candidate for terminally supporting a subsequent codec-bypass negotiation with the originating entity;
- responsive to the assessment of compatibility being negative, self-identifying the gateway as a candidate for non-terminally supporting a subsequent codec-bypass negotiation with the originating entity.

18. A method of establishing a codec-bypass connection between a first gateway and one of a plurality of in-path gateways located along a path from the first gateway to a second gateway, comprising:

- identifying a target in-path gateway from among the plurality of in-path gateways, the target in-path gateway being the in-path gateway furthest along the path from the first gateway which is characterized by codec-bypass connection compatibility with the first gateway;
- 5 - establishing a codec-bypass connection between the first gateway and the target in-path gateway.

19. The method defined in claim 18, further comprising:

- 10 - performing a determination of whether the target in-path gateway is involved in a prior codec-bypass connection with the second gateway;
- wherein performing the establishing is conditional upon said determination being negative.

20. The method defined in claim 19, the target in-path gateway being a first target in-path gateway, the method further comprising:

- 15 - responsive to said determination being positive:
 - identifying a second target in-path gateway from among the plurality of in-path gateways, the second target in-path gateway being the in-path gateway furthest along the path from the first gateway which is characterized by codec-bypass connection compatibility with the first gateway and which is not involved in a
 - 20 codec-bypass connection with the second gateway;
- establishing a codec-bypass connection between the first gateway and the second target in-path gateway instead of with the first target in-path gateway.

25 21. The method defined in claim 18, further comprising:

- performing a determination of whether the target in-path gateway is involved in a prior codec-bypass connection with the second gateway;
- wherein performing the establishing is conditional upon said determination being
- 30 negative.

22. A method of establishing a codec-bypass connection along a path between a first gateway and a second gateway, the path comprising a plurality of in-path gateways, comprising:

- identifying a first sub-path between the first gateway and a first target in-path gateway from among the plurality of in-path gateways, the first target in-path gateway being the in-path gateway furthest along the path from the first gateway which is characterized by codec-bypass connection compatibility with the first gateway;
- identifying a second sub-path between the second gateway and a second target in-path gateway from among the plurality of in-path gateways, the second target in-path gateway being the in-path gateway furthest along the path from the second gateway which is characterized by codec-bypass connection compatibility with the second gateway;
- determining the lengths of the first and second sub-paths;
- if the first sub-path is longer than the second sub-path, establishing a codec-bypass connection between the first gateway and the first target gateway;
- if the second sub-path is longer than the first sub-path, establishing a codec-bypass connection between the second gateway and the second target gateway.

23. The method defined in claim 22, further comprising:

- if the first sub-path is not longer than the second sub-path and the second sub-path is not longer than the first sub-path:
- determining the priorities of the codec-bypass connection compatibility of the first target gateway with the first gateway and of the second target gateway with the second gateway and:
 - if the codec-bypass connection compatibility of the first target gateway with the first gateway has a greater priority than the codec-bypass connection compatibility of the second target gateway with the second gateway, establishing a codec-bypass connection between the first gateway and the first target gateway;
 - if the codec-bypass connection compatibility of the second target gateway with the second gateway has a greater priority than the codec-bypass connection compatibility of the first target gateway with the first gateway, establishing a codec-bypass connection between the second gateway and the second target gateway.




FIG. 1A

2/7




FIG. 1B





FIG. 1C




4/7

FIG. 1D

5/7

FIG. 2






FIG. 3




FIG. 4







FIG. 5



INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA2004/000300

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04Q7/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	ETSI: "Digital cellular telecommunications system (Phase 2+); Inband Tandem Free Operation (TFO) of Speech Codecs; Service Description; Stage 3 (GSM 04.53 version 1.6.0)" GSM GLOBAL SYSTEM FOR MOBILE TELECOMMUNICATIONS, 'Online! October 1998 (1998-10), pages 1-69, XP002283034 Retrieved from the Internet: URL: http://www.3gpp.org/ftp/Specs/html-inf/o/0453.htm 'retrieved on 2004-06-02! page 14, line 21 - page 15, line 18 page 29, line 26 - page 30, line 14 table 10	1,2,4-7, 16-18
A	----- --/--	3,8-15, 19-23

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

* & * document member of the same patent family

Date of the actual completion of the international search

15 June 2004

Date of mailing of the international search report

15/07/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Alonso Maleta, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA2004/000300

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	ETSI: "Digital Cellular telecommunication system (phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); Inband Tandem Free Operation (TFO) of speech codecs; Service Description; Stage 3 (3GPP TS 28.062 version 5.0.0 Release 5)" ETSI TS 128 062 V5.0.0, XX, XX, March 2002 (2002-03), pages 14-19, 35-51, 56-59, 81-88, 164-168, XP002248624 page 36, line 4 - page 37, line 9 page 40, line 4 - line 22 page 45, line 4 - line 15	1,2, 16-18
A		3-15, 19-23
A	----- WO 00/51330 A (ERICSSON TELEFON AB L M) 31 August 2000 (2000-08-31) page 1, line 11 - line 14 page 3, line 7 - page 5, line 9 page 6, line 8 - line 20 page 12, line 7 - page 13, line 9 claims 14,30	1-23
A	----- WO 00/70885 A (ERICSSON TELEFON AB L M) 23 November 2000 (2000-11-23) page 3, line 6 - page 4, line 19 page 19, line 17 - page 20, line 20	1-23
A	----- WO 01/26390 A (ERICSSON INC) 12 April 2001 (2001-04-12) page 2, line 5 - page 3, line 29 page 8, line 12 - page 9, line 30 -----	1-23

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CA2004/000300

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0051330	A	31-08-2000	AU 2804300 A	14-09-2000
			WO 0051330 A1	31-08-2000
			EP 1155559 A1	21-11-2001
			JP 2002538679 A	12-11-2002
WO 0070885	A	23-11-2000	GB 2350257 A	22-11-2000
			GB 2351414 A	27-12-2000
			GB 2351416 A	27-12-2000
			GB 2352127 A	17-01-2001
			AU 4919700 A	05-12-2000
			CN 1361994 T	31-07-2002
			WO 0070885 A1	23-11-2000
			EP 1179264 A1	13-02-2002
			GB 2350261 A	22-11-2000
			JP 2003500907 T	07-01-2003
			US 6671367 B1	30-12-2003
			US 2004101125 A1	27-05-2004
WO 0126390	A	12-04-2001	US 6600738 B1	29-07-2003
			AU 7839600 A	10-05-2001
			CN 1382348 T	27-11-2002
			EP 1219120 A1	03-07-2002
			JP 2003511922 T	25-03-2003
			WO 0126390 A1	12-04-2001